



Benchmark Example No. 57

Response Spectrum Analysis of a Simply Supported Beam

VERiFiCATION
BE57 Response Spectrum Analysis of a Simply Supported Beam

VERiFiCATION Manual, Service Pack 2022-12 Build 74

Copyright © 2023 by SOFiSTiK AG, Nuremberg, Germany.

SOFiSTiK AG

HQ Nuremberg
Flataustraße 14
90411 Nürnberg
Germany

T +49 (0)911 39901-0
F +49(0)911 397904

Office Garching
Parkring 2
85748 Garching bei München
Germany

T +49 (0)89 315878-0
F +49 (0)89 315878-23

info@sofistik.com
www.sofistik.com

This manual is protected by copyright laws. No part of it may be translated, copied or reproduced, in any form or by any means, without written permission from SOFiSTiK AG. SOFiSTiK reserves the right to modify or to release new editions of this manual.

The manual and the program have been thoroughly checked for errors. However, SOFiSTiK does not claim that either one is completely error free. Errors and omissions are corrected as soon as they are detected.

The user of the program is solely responsible for the applications. We strongly encourage the user to test the correctness of all calculations at least by random sampling.

Front Cover

Arnulfsteg, Munich Photo: Hans Gössing

Overview

Element Type(s):

Analysis Type(s):

Procedure(s):

Topic(s): EQKE

Module(s): DYNA

Input file(s): [response_spectrum_analysis.dat](#)

1 Problem Description

The following example is focused on the results of a response spectrum analysis of a simply supported beam, with the problem description defined by [1]. A simple beam with a rectangular cross section, shown in Fig.1a, is subjected to a vertical movement of its supports according to the acceleration history shown in Fig.1b. The acceleration changes linearly from g to $-g$ within a time period of $2t_d$, and is zero afterwards, with g being the gravitational acceleration.

The response of the system is determined based only on the first eigenmode. Therefore, modal superposition is not carried out in this example. Furthermore, zero damping of the system is assumed.




Figure 1: (a) Simply supported beam; (b) Acceleration history

The acceleration of a mass in a SDOF spring-mass system subjected to the base acceleration history from Fig.1b is defined as follows [1], for $t \leq 2t_d$:

$$\ddot{u} = g \left(1 - \cos \omega t + \frac{\sin \omega t}{\omega t_d} - \frac{t}{t_d} \right) \quad (1)$$

and for $t > 2t_d$:

$$\ddot{u} = \ddot{u}_{t=2t_d} \cos \omega(t - 2t_d) + \dot{u}_{t=2t_d} \frac{\sin \omega(t - 2t_d)}{\omega} \quad (2)$$

where ω is the circular eigenfrequency.

2 Reference Solution

In the first step of the response spectrum analysis, the eigenfrequency of the first eigenmode is calculated as follows [1]:

$$f = \frac{\pi}{2l^2} \sqrt{\frac{EI_y}{m}} \quad (3)$$

where l is the length and m is the mass per unit length of the beam, and EI_y is the bending stiffness.

Based on the calculated eigenfrequency, the maximum relative displacement of the equivalent SDOF system, $u_{max,0}$, is determined from the corresponding response spectrum [1]. Subsequently, the maximum beam deflection is calculated [1]:

$$u_{max} = \Gamma u_{max,0} \quad (4)$$

The shape function for the first eigenmode $\Phi(x)$ is given by [1]

$$\Phi(x) = \sin \frac{\pi x}{l} \quad (5)$$

, and the modal participation factor Γ is calculated as:

$$\Gamma = \frac{\int_0^l m \Phi(x) dx}{\int_0^l m [\Phi(x)]^2 dx} = \frac{4}{\pi} \quad (6)$$

The bending moment is defined as follows [1]:

$$M_x = -EI_y \frac{\partial^2 u(x)}{\partial x^2} \quad (7)$$

where $u(x)$ is the beam deflection for the first eigenmode

$$u(x) = u_{max} \sin \frac{\pi x}{l} \quad (8)$$

Therefore, the maximum bending moment in the middle of the span is computed as:

$$M_{y,max} = \frac{EI_y \pi^2}{l^2} u_{max} \quad (9)$$

3 Model and Results

Material, geometry and loading properties of the beam model defined in a plane system are summarized in Table 1.

Table 1: Model Properties

Material Properties	Geometric Properties	Loading
$E = 206842 \text{ MPa}$	$l = 6.096 \text{ m}$	$g = 10 \text{ m/s}^2$
$\rho = 104730 \text{ kg/m}^3$	$h = 35.56 \text{ mm}$	$t_d = 0.1 \text{ s}$
	$b = 3.7026 \text{ mm}$	

The response spectrum values are calculated as maximum acceleration values, in the units of g , from the Equations 1 and 2 as a function of the eigenperiod. For the purpose of this example, only the values in the proximity of the system's first eigenperiod are taken as the input points of the response spectrum. The selected points are listed in Table 2 and also shown on the graph of the response spectrum, which is plotted as a function of the eigenfrequency in Figure 2.

Table 2: Calculated points of the response spectrum

Eigenfrequency [Hz]	Eigenperiod [s]	Max. acceleration [g]
5.00	0.20	2.000000
5.50	0.181818	1.818181
6.00	0.166667	1.666667
6.05	0.165289	1.652893
6.10	0.163934	1.639344
6.15	0.162602	1.626016
6.50	0.1538461	1.538461
7.00	0.142857	1.428571




Figure 2: The response spectrum and the selected input points

The calculated values of the eigenfrequency f of the first mode, and the maximum deflection u_{max} and the bending moment $M_{y,max}$ in the middle of the span as a result of the response spectrum analysis, are compared with the reference values in Table 3.

Table 3: Results

	SOF.	Ref. [1]
f [Hz]	6.12	6.10
u_{max} [mm]	14.15	14.22
$M_{y,max}$ [kNm]	108.03	108.41

4 Conclusion

A very good agreement between the reference solution and the numerical results calculated by SOFiSTiK verifies the implementation of the response spectrum analysis.

5 Literature

[1] J.M. Biggs. *Structural Dynamics*. McGraw-Hill, 1964.